



Reflectix® Sill Sealer

Made from ribbed, closed-cell, polyethylene foam, Reflectix® Sill Sealer was designed to reduce air leakage between the foundation wall and sill plate. Our Sill Sealer can also be used as a seal around windows and doorframes.

Product Features:

- Convenient roll sizes
- Easy installation

Product Benefits:

- Air and moisture barrier
- Stops heat loss and air infiltration at the foundation to sill plate interface
- Eliminate costly callbacks to builders due to leaks
- Mildew and water-resistant
- Provides protection against sill plate rot
- Highly durable
- Works on residential and commercial construction, slab on grade, crawl spaces or basements

All rolls are 50' in length and come in a variety of widths: 3.5", 5.5", 7.5" and 9.5"

Reflectix, Inc. #1 School St. (POB 108) Markleville, IN 46056

Ph: (800) 879-3645 (US/Can) • (765) 533-4332

Fax: (765) 533-2327

Email: customerservice@reflectixinc.com

www.reflectixinc.com

www.youtube.com/ReflectixInsulation

www.facebook.com/ReflectixInsulation

www.pinterest.com/reflectixinc

F13 Rev 0118



Technical Data:

Physical Properties*:	Test Method:	CA 185 CF:
Nominal Thickness	ASTM D3575 Suffix B	3/16"
Compressive Strength - Vertical Direction (psi) (plied to 1 inch)	ASTM D3575 Suffix D @ 25%/50%	1.5 7.5
Compression Set (%)	C.I.D. A-A 59135	< 10%
ASTM D3575 Tensile Strength (psi)	17 Suffix T MD / CD	53
ASTM D3575 Elongation (%)	40 Suffix T MD / CD	55
ASTM D3575 Tear Resistance (lb/in)	9.5 Suffix T MD / CD	4.5
Water Absorption (lb.ft ²)	ASTM D3575 Suffix L	< 0.1
Thermal Stability (%)	ASTM D3575 Suffix S	< 2

* The data presented for this product is for unfabricated polyethylene foam product. While the values shown are typical of this product, they should not be constructed as specification limits. (12/03)